UNCLASSIFIED AD 431307

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

431307

U.S. ARMY

TRANSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

TRECOM TECHNICAL REPORT 63-70

IMPERVIOUS TURBULENT BOUNDARY LAYER
MEASUREMENTS USING AN INTEGRATING
BOUNDARY LAYER MOUSE

Task 1D121401A14203 Contract DA 44-177-AMC-892(T)

November 1963

prepared by:

MISSISSIPPI STATE UNIVERSITY The Aerophysics Department State College, Mississippi



NOTICES

DISCLAIMER NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission, to manufacture, use, or sell any patented invention that may in any way be related thereto.

DDC AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from

Defense Documentation Center Cameron Station Alexandria, Virginia 22314

This report has been released to the Office of Technical Services, U. S. Department of Commerce, Washington 25, D. C., for sale to the general public.

The findings and recommendations contained in this report are those of the contractor and do not necessarily reflect the views of the U. S. Army Mobility Command, the U. S. Army Materiel Command, or the Department of the Army.

HEADQUARTERS U.S. ARMY TRANSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

The study represented by this report was conducted in an attempt to devise a system whereby turbulent boundary layer data could be more readily obtained and interpreted into usable parameters. Specifically, the investigation concentrated on the use of a single composite boundary layer mouse to simplify data recording and computation. Results from the laboratory investigation indicated that the composite boundary layer mouse provided measurements well within experimental accuracy of standard boundary layer velocity profile measurements.

It was concluded that although the composite integrating mouse would not replace the usual velocity profile measuring systems, it would significantly add to the methodology of boundary layer research.

GARY N. MITH

Project Engineer

PAUL J CARPENTER

Group Leader

Applied Aeronautical Engr Group

APPROVED.

FOR THE COMMANDER:

TAPPY M HEWTH

Technical Director

Task 1D121401A14203 Contract DA 44-177-AMC-892(T) TRECOM Technical Report 63-70 November 1963

IMPERVIOUS TURBULENT BOUNDARY LAYER
MEASUREMENTS USING AN INTEGRATING
BOUNDARY LAYER MOUSE

Aerophysics Research Note No. 17

Prepared by
The Aerophysics Department
Mississippi State University
State College, Mississippi

for U. S. ARMY TRANSPORTATION RESEARCH COMMAND FORT EUSTIS, VIRGINIA

CONTENTS

	Page
LIST OF ILLUSTRATIONS	 iv
LIST OF SYMBOLS	 v
INTRODUCTION	 1
THEORETICAL DEVELOPMENT OF COMPOSITE SYSTEM	 2
DESCRIPTION OF APPARATUS AND EXPERIMENTAL TECHNIQUES	 6
DISCUSSION OF RESULTS	 7
CONCLUSIONS	 9
REFERENCES	 10
ILLUSTRATIONS	 11
DISTRIBUTION	 19

SYMBOLS

x, y	Co-ordinates
H	Total head
p	Static pressure
h	Height of integrating rake
e	Density
8	Boundary layer thickness
8*	Displacement thickness
V	Kinematic viscosity
0	Momentum loss thickness
4	Boundary layer parameter
Kr Uz	Preston tube calibration constant
UZ	Friction velocity
20	Surface shearing stress
Ro	Reynolds number
Vu	Velocity component due to wake
R5*+0	Reynolds number
/ -	= 6
Subscript	s

Freestream conditions

Conditions at sea level

Local conditions at outer edge of boundary layer Ĺ

ILLUSTRATIONS

Figure		<u>Page</u>
1	Composite Boundary Layer Mouse	11
2	Diagrammatic Layout of Composite System	11
3	Preston Tube Calibration Curves	12
4	Chart of R θ and R $\beta^* \!$	13
5	Composite Mouse on the Test Section	14
6	Velocity Distribution Over the Test Section	14
7	Comparison of Results From the Two Systems, $U_{\infty} = 50$ MPH, $\alpha = 10.5^{\circ}$	15
8	Comparison of Results From the Two Systems, $U_{\infty} = 90$ MPH, $\propto = 2.0^{\circ}$	16
9	Comparison of Results at a Constant Chord Position; 75 Per Cent of Chord	17
10	Comparison of Results at a Constant Chord Position; 85 Per Cent of Chord	18

INTRODUCTION

To obtain the parameters which describe a turbulent boundary layer, it is usual to measure the boundary layer velocity profile from which can be computed, using standard techniques, such parameters as the momentum loss thickness, displacement thickness, and the surface shear. The velocity profile can be obtained using either a multitube total head "mouse" connected to a multitube water manometer or a single Pitot-static system connected to an airspeed indicator which can be raised above the surface by a calibrated micrometer screw. The former method tends to be inaccurate because of the limitations on the number cf tubes and the difficulties of measuring the 'y' value accurately, and the latter method is really applicable only to wind tunnel testing where the test surface is the tunnel wall. An externally mounted screw arrangement can be fixed to the test surface; but the time taken to obtain a single profile is appreciable, and also the corrections due to the presence of the traversing mechanism on the test surface may have to be taken into consideration. The process of obtaining the boundary layer parameters from the velocity profiles is slow if performed by hand computation or expensive if programmed for a digital computer. In either case, the complete test program is slowed down due to the time lag between the experiments and the finished results.

This report deals with an attempt at devising a system for determining the turbulent boundary layer data using a single composite boundary layer mouse, which requires simultaneous reading of three airspeed indicators and from which all pertinent parameters of the boundary layer can be easily and simply computed, thereby reducing both testing and data reduction time.

THEORETICAL DEVELOPMENT OF COMPOSITE SYSTEM

It is known that if three quantities of a boundary layer on an impervious surface are known, then the remaining quantities can be found from predetermined relationships. The difficulty of obtaining one reading which is proportional to either velocity defect or momentum loss over the entire boundary layer thickness may be overcome by using an integrating boundary layer mouse connected against the local total head (Figure 2) such that

$$\Delta P = \frac{1}{h} \int_{0}^{h} (H_{L} - H) dy$$

$$IF h > S \text{ THEN } (H_{L} - H) = 0$$

$$\Delta P = \frac{1}{h} \int_{0}^{\infty} (H_{L} - H) dy$$

$$\therefore \Delta P = \int_{0}^{\infty} (P_{L} + \frac{1}{2} P U_{L}^{2} - P - \frac{1}{2} P U_{L}^{2}) dy.$$

Assuming that the static pressure is constant through the boundary layer and that the flow is incompressible, then $p = p \perp$ and $P = e_{\perp}$.

$$i. \Delta p = \frac{\rho}{2h} \int_0^\infty (U^2 - u^2) dy$$

$$= \frac{\rho}{2h} \int_0^\infty \left[U(U - u) + u(U - u) \right] dy$$

$$= \frac{\rho U^2}{2h} \int_0^\infty \left[\left(1 - \frac{u}{U} \right) + \frac{u}{U} \left(1 - \frac{u}{U} \right) \right] dy$$

$$= \frac{\rho U^2}{2h} \left(\int_0^\infty \left(\int_0^\infty + \theta \right) dy \right)$$

As dp is measured using an airspeed indicator (m.p.h.), then

$$\Delta p = \frac{1}{2} e (1.467 U_i)^2.$$
herefore $e_0 (1.467 U_i)^2 = \frac{eU^2}{h} (5*+\theta)$
and $e_0 (1.467 U_i)^2 = \frac{eV^2}{h} (5*+\theta) = \frac{eV^2}{h} (1.467)^2$.

A local freestream Pitot-static system (Figure 2) can be used such that

$$U_2 = \frac{U}{1.467}$$
 (ii)

Also, a calibrated Preston tube surface shear meter will give U_3 where

$$U_3 = \frac{1}{K_T} U_T$$
 (iii)

Ky is a function of diameter ratios, altitude, density, and boundary thickness. Curves of 3 against by for various altitudes appropriate for a particular Preston tube have been calculated and drawn in Figure 3. Then

$$(8*+0) = \frac{h}{\tau} \left(\frac{U_1}{U_2}\right)^2$$
 WHERE $\tau = \frac{\rho}{C_0}$

and

$$R(s*+0) = \frac{(s*+0)U}{V} = \frac{h}{V} \frac{1.467}{V} \frac{U_1^2}{U_2};$$
 (iv)

also

$$\frac{U_T}{U} = \frac{K_T U_3}{1.467 U_5} . \tag{v}$$

Knowing $\mathcal{R}(\mathcal{F}_{+}\mathcal{F}_{0})$ and $\frac{\mathcal{F}_{+}}{\mathcal{F}_{0}}$, $\frac{\mathcal{F}_{+}}{\mathcal{F}_{0}}$ can be obtained from Figure 4, which is a plot of the following equations from Reference 1.

Hence, using $\frac{U\tau}{U}$ and $\frac{U\omega}{U\tau}$, Ro can also be found from Figure 4, from which θ and, together with equation iv, S^* can be determined.

 \mathcal{S} , if needed, can be calculated using the following equation from Reference 1.

$$\delta = \frac{\omega}{U_T} \log^{-1} \left[\frac{1}{5.6} \left(\frac{U}{U_T} - \frac{U_{\infty}}{U_T} \right) \right]$$
 (viii)

This means that all the following quantities about the boundary layer are known.

Similarly, if the integrating system is connected against the local static pressure instead of the total head, then

$$\Delta P = \frac{1}{h} \int_{0}^{\infty} (H - P_{2}) dy$$

$$= \frac{1}{2} \left(\frac{1}{h} \right) \int_{0}^{\infty} u^{2} dy$$

$$= -\frac{\rho}{2h} \int_{0}^{\infty} (U^{2} - u^{2} - U^{2}) dy$$

$$= -\frac{\rho}{2h} \int_{0}^{\infty} [U(U - u) + u(U - u) - U^{2}] dy$$

$$= -\frac{ev^{2}}{2h} \left[\left(1 - \frac{u}{v} \right) + \frac{u}{v} \left(1 - \frac{u}{v} \right) - 1 \right] dy$$

$$= -\frac{ev^{2}}{2h} \left(s^{*} + \theta - h \right)$$

$$\therefore \frac{1}{2} e \left(1.467 U_{i} \right)^{2} = -\frac{ev^{2}}{2h} \left(s^{*} + \theta - h \right)$$

$$U_{i}^{2} = -\left(\frac{e}{e} \right) \frac{V^{2}}{(1.467)^{2}} \frac{\left(s^{*} + \theta - h \right)}{h}$$
(ix)

as in previous case

$$U_2 = \frac{U}{1.467}$$
 (ii)

and

$$U_2 = \frac{U_7}{K_7}$$
 (iii)

giving

$$R_{S+0} = \frac{1467 \frac{U_2 h}{z}}{z} \left[1 - \frac{1}{\sqrt{\left(\frac{U_2}{U_2}\right)^2}} \right]. \tag{x}$$

The remaining unknowns are calculated as in the previous case.

DESCRIPTION OF APPARATUS AND EXPERIMENTAL TECHNIQUES

The composite boundary layer mouse consists of fifty equally spaced total head tubes over a total range of 2.44 inches. Above the integrating rake, two total head tubes were fixed which sensed the local freestream total head; two static pressure taps and a calibrated Preston tube were on the bottom of the rake, with the Preston tube touching the surface during the tests. The integrating rake could be connected against either the local static pressure or the local total head. The equations for both methods were developed in the previous chapter. The local static pressure was connected against the freestream total head and the Preston tube, and lightly damped Kollsman helicopter airspeed indicators were used to measure the pressure differences. Great care was taken to balance dynamically all the systems of the composite boundary layer mouse for rate of change of pressure.

To check the results using this composite system, the boundary layer velocity profiles were measured by use of the standard multitube boundary layer mouse connected to a multitube photographic water manometer, and the boundary layer parameters were determined by hand computation. The comparison results are presented in graphical form in Figures 7, 8, 9, and 10.

The tests were performed on a fiberglass test section on the port wing of a Schweitzer TG-3 sailplane. The comparison tests were carried out on different chordwise stations of the section at different aircraft airspeeds, simulating various pressure gradients and boundary layer thicknesses. The maximum altitude range of the tests was from 5,000 feet to sea level in smooth turbulence-free air with a maximum Reynolds number variation of two per cent. The airspeed indicator readings together with pressure altitude and outside air temperature were radioed to the ground during the tests.

DISCUSSION OF RESULTS

The composite boundary layer mouse is well suited to aircraft and wind tunnel use if care is taken to ensure that the Preston tube touches the surface and that the tubes of the integrating rake are evenly spaced. Adequate adjustment was available by means of the rear supporting arm to always maintain the plane of measurement perpendicular to the surface, irrespective of airfoil curvature. Preliminary experiments were performed using a common static source for both the local total head and the Preston tube, but the integrating effect of this common static source gave very misleading results and an additional static source was mounted on the mouse. Great care in dynamically balancing the three systems is necessary to prevent errors due to rate of change of pressure that are associated with experiments on sailplanes.

The results obtained using the composite mouse agreed remarkably well with those obtained using the multitube mouse, the maximum differences being of the order of 5 per cent in the case of $\checkmark_{\mathcal{T}}$ and about 4 per cent in the measurement of δ , δ and θ . It must be emphasized that these differences are within the experimental errors associated with using a multitube mouse and a photographic water manometer to obtain boundary layer velocity profiles. It can be seen that as the boundary layer thickness decreases, the errors in the δ and θ results tend to increase, which is to be expected because of the decrease in sensitivity of the integrating rake with decrease in boundary layer thickness.

The maximum error is in the determination of the skin friction velocity; and as this was measured using a Preston total head tube, some doubt must be cast upon this method of determining skin friction. Nevertheless, the accuracy is adequate to use \mathcal{U}_{i} in equation (iv) to obtain from the chart the values of \mathcal{S}^{*} and \mathcal{O} . It would appear that \mathcal{O}_{i} is a weak function in the boundary layer equations to obtain \mathcal{R}_{i} and \mathcal{R}_{i} and \mathcal{R}_{i} and \mathcal{R}_{i} and \mathcal{R}_{i} is to insert the experimental values of \mathcal{O}_{i} , \mathcal{O}_{i} and \mathcal{R}_{i} , which are within a per confined those obtained using the profile techniques, into the shear relationship by Ludweig and Tillmann.

$$\left(\frac{U_T}{U}\right)^2 = \frac{0.123}{\left(\frac{U_0}{U}\right)^{.260} .678H}$$
 (xi.)

We was calculated using equation xi for both the 75 per cent and the 85 per cent chord positions and plotted in Figures 9 and 10. The Ludweig and Tillmann results fall below those of the profile method,

indicating that the Preston tube results may be in error by as much as 12 per cent. This means that to obtain very accurate values of U_7 , θ and H are found from the composite mouse and then inserted into the Ludweig and Tillmann shear relationship.

Using the composite boundary layer mouse, it was quite usual for the values of \mathcal{S}^{*} , \mathcal{O} and \mathcal{H} to be calculated and plotted while the aircraft was descending from the test altitude, whereupon the results were presented to the test engineer immediately on landing. This system enabled the plotting of pertinent turbulent boundary layer parameters over a total section to be obtained in a very short time with continual monitoring of the results.

CONCLUSIONS

The composite boundary layer mouse was found to be a very accurate and convenient instrument to use in flight experiments to determine turbulent boundary layer parameters on an impervious surface. The system could be used in wind tunnel testing, but it would be necessary to decrease the height of the integrating rake to increase the sensitivity for the thin boundary layers associated with small wind tunnel experiments.

The accuracy of the system in comparison with the profile method was well within the experimental tolerances usual with the measurement of boundary layer velocity profiles. The skin friction results obtained using the Preston shear meter were not quite so accurate, but this deficiency could be overcome by using the Ludweig and Tillmann shear relationship to obtain $\mathcal{L}_{\mathcal{T}}$.

The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire research program.

As a large number of turbulent boundary layer theories attempt to predict the mean velocity profile of a turbulent layer, and as these theories must be verified, the composite integrating mouse which cannot perform this task can never completely replace velocity profile measuring systems. Nevertheless, it can be used as a powerful tool in boundary layer research.

REFERENCES

- Cornish, J. J., III, <u>A Universal Description of Turbulent Boundary Layer Profiles with or without Transpiration</u>, Aerophysics Department, Mississippi State University, Report No. 29, June 1960.
- 2. Clauser, F. H., "Trubulent Boundary Layer," Advances in Applied Mechanics, IV, New York, 1956.
- Preston, J., "The Determination of Turbulent Skin Friction by Means of Pitot Tubes," <u>Journal of the Royal Aeronautical Society</u>, Vol. 58, No. 518, February 1954.
- 4. Ludweig, H., and Tillmann, W., <u>Investigation of the Wall Shearing</u>

 <u>Stress in Turbulent Boundary Layers</u>, NACA Tech. Memo No. 1285,
 1950.




Figure 1. Composite Boundary Layer Mouse.




Figure 2. Diagrammatic Layout of Composite System.





Figure 3. Preston Tube Calibration Curves.






Figure 5. Composite Mouse on the Test Section.




Figure 6. Velocity Distribution Over the Test Section.




Figure 7. Comparison of Results From the Two Systems, $U_{\infty}=50~\mathrm{MPH},~\propto=10.5^{\circ}.$




Figure 8. Comparison of Results From the Two Systems, U_ ∞ = 90 MPH, \ll = 2.0°.




Figure 9. Comparison of Results at a Constant Chord Position, 75 Per Cent Chord.




Figure 10. Comparison of Results at a Constant Chord Position, $\,$ 85 Per Cent Chord.

DISTRIBUTION

Army Research Office, Durham	2
Office of Chief of R&D, D/A]
Naval Air Test Center	j
Army Research Office, OCRD	J
U. S. Army Aviation and Surface Materiel Command	1
U. S. Army Transportation Research Command	19
Office of the United States Army Attache]
U. S. Army Research and Development Group (Europe)	1
Air University Library, Maxwell AFB]
Bureau of Naval Weapons]
U. S. Naval Postgraduate School	3
U. S. Army Standardization Group, Canada	1
Canadian Liaison Officer,	
U. S. Army Transportation School	1
British Army Staff, British Embassy]
U. S. Army Standardization Group, U. K.]
NASA-LRC, Langley Station	2
Ames Research Center, NASA	2
Lewis Research Center, NASA]
Scientific and Technical Information Facility	6
Defense Documentation Center	10
U. S. Army Mobility Command	2
U. S. Army Materiel Command	2
Chief of Transportation, D/A	1

Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULEMT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task 1D121401A14203.	Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task ID121401A14203.	l. Turbulent Boundary Layer Measurements
Unclassified Keport The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	Unclassified Keport The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	
Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task 1D121401A14203.	Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task ID121401A14203.	l. Turbulent Boundary Layer Measurements
Unclassified Report	Unclassified Report	
The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	

the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by amy computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduction which reduction time, and thereby appreciably speeded up the entire boundary layer research program.

meters of a turbulent boundary layer. The accuracy of the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

Turbulent Boundary Layer Measurements		Turbulent Boundary Layer Measurements		
		ri e		
Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task 1D121401A14203.	Unclassified Report The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(I)) USATRECOM Task ID121401A14203.	Unclassified Report	The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-
Turbulent Boundary Layer Measurements		Turbulent Boundary Layer Measurements		
Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task 1D121401A14203.	Unclassified Report The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-	Mississippi State University, Aerophysics Department, IMPERVIOUS TURBULENT BOUNDARY LAYER MEASUREMENTS USING AN INTEGRATING BOUNDARY LAYER MOUSE - Sean C. Roberts, Research Note 17, TRECOM Technical Report 63- 70, November 1963, 19 pp. (Contract DA 44-177-AMC-892(T)) USATRECOM Task 1D121401A14203.	Unclassified Report	The composite boundary layer mouse is an alternative method to the boundary layer velocity profile technique of determining all the pertinent para-

the system in comparison with the profile method was well within experimental colerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

meters of a turbulent boundary layer. The accuracy of the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduced the data reduction time, and thereby appreciably speeded up the entire boundary layer research program.

the system in comparison with the profile method was well within experimental tolerances usual with the measurement of boundary layer velocity profiles. The use of the composite system simplified the data reduction which could be performed by any computer, reduction which reduction time, and thereby appreciably speeded up the entire boundary layer research program.

UNCLASSIFIED

UNCLASSIFIED